# AIR-CHANNEL<sup>®</sup> CLASSIC




## WITH SUBFLOOR

## STABILITY, PERFORMANCE AND LONGEVITY

Air Channel Classic takes commodity floating sleeper system technology and adds a whole new dimension of resilience and uniformity. This economical suspended system features enhanced pad components for added value in a basic commodity design. The double profiled, cavity-backed, 7/16" EPDM rubber Bio-Pads offers greater durability and higher performance values than most commodity pad designs.

- 1. Finish: MFMA approved floor finish
- 2. Gamelines: Gameline Paint
- 3. Sealer: MFMA approved floor sealer



SPORTS SURFACES

- 4. Flooring: Commodity 25/32" (20mm) Random Length (RL) Northern Hard Strip Maple or upgraded Continuous Strip® XL Finger-Jointed(FJ) Northern Hard Strip Maple
- 5. Flooring Fastener: 2" staples or flooring cleats
- 6. Subfloor: 1 layer of nominal 1/2" x 48" x 96" (12mm x 122 cm x 244cm) Exposure 1 rated subfloor sheathing stapled to sleepers
- 7. Sleeper: Nominal 2" x 3" x 4' long fir or pine.
- 8. Resilient Pad: 7/16" EPDM Bio-Pad
- 9. Vapor Barrier: 6- MIL polyethylene

#### System Benefits:

- 7/16" (11mm) resilient EPDM Bio-Pad<sup>™</sup> for shock absorption and vibration control
- Continuous Strip® XL Maple adds strength and provides a floor that can last up to 10 years longer than random-length strip
- Continuous subfloor provides uniformity & strength under bleacher loads and portable backstops
- High-Profile
- Economical
- Other pad options

robbinsfloor.com | 1.800.543.1913



## AIR-CHANNEL<sup>®</sup> CLASSIC


## WITH SUBFLOOR



## **Product Specifications**

. . .

Product Specifications		
<b>O</b> System Type	Floating	3" (76mm) x 4" (102m
<b>O</b> Slab Depression	3 ¼" (79mm) with 25/32" (20mm) thick Maple 3 ¾" (86mm) with 33/32" (26mm) thick Maple	Threshold View
<b>O</b> Surface- MFMA Northern Hard Maple	Robbins Continuous Strip <sup>®</sup> XL (FJ) or Random Length (RL)	1.5*- 2* (38mm-51n 1/4* (6mm)Thresh
<b>O</b> LEED Contributions <b>V</b> <b>V</b> <b>V</b> <b>V</b> <b>V</b> <b>V</b> <b>V</b> <b>V</b>	MR credit 4, 5, & 7 IEQ 4.1, 4.2, 4.3, 4.4 FSC <sup>®</sup> Lumber Available *Credits are based on products selected and location of facility	Equipment View Insert Plat 1.5°, 2° (88mm51mm) 25/32° (20mm) Magie Flooring Magie Flooring 6 ML Vapor Barrier
Subfloor Construction	Sleeper with Subfloor	Concrete Slab
<b>O</b> Resilience Layer	EPDM Bio-Pad	
Optional Construction	Contact a Robbins Representative for Alternative Systems	
Warranty Egis	1 year Industry Standard with optional Extended Warranty Program ( <i>Egis Floorlife</i> )	
O Air-Channel Family Reference Facilities	Oklahoma University University of Mississippi Robert F. Kennedy High School	
robbinsfloor.com   1.800.543.1913		



Wall View

